






# Strom

The Strom will fit into most ceilings (T-grid, plasterboard and metal tile) even in applications with restricted ceiling voids. A general use fitting that suits neutral space with clean lines. The Strom is especially suited to offices, schools and healthcare space with lower ceiling heights (<2.7m) where good uniformity is required.

- Virtual Daylight® specification
- Minimal ceiling void required
- Lumafix fixing brackets

## Strom





Product	Available Options	Power	Weight	Height	Width	Cutout
SR3-218	-DSI,-110,-DALI,-SD,-EMR	2 x 18w	5.2kg	80	350 x 350	310 x 310
SR3-226	-DSI,-110,-DALI,-SD,-EMR	2 x 26w	5.5kg	80	350 x 350	310 x 310

Options	Code Suffix
Dimming - DSI	-DSI
Dimming - 110	-110
Dimming - DALI	-DALI
Dimming - Switchdim	-SD
3hr Remote Emergency Facility	-EMR

Light Source	Code		Power	Lampholder	Colour Temp	Output
	ILCOS	LBS				
Compact Fluorescent	FSQ-18-E	TC-DEL	18w	G24q-2	860	1200 lm
Compact Fluorescent	FSQ-26-E	TC-DEL	26w	G24q-3	860	1800 lm

Accessories	Code Suffix
Ceiling Support Pattress	-PAT