

## Clearvision Lighting - Specification

### Darkstar 95 F:

A recessed single lamp 97mm diameter x 100mm deep tilt/rotational spotlight to suit a 80mm ceiling cut out. Die-cast, powder-coated white (RAL 9010) aluminium bezel. Spun, black painted aluminium, anti-glare, barrel. Magnetically held, fully 360 degree rotating bezel. 2-way terminal block with clip-close enclosure, located on a steel mounting arm. 2off sprung steel fixing arms suitable for ceilings of up to 25mm thickness. Supplied with dimmable electronic transformer to operate a single 20-50w MR16 (50mm dia.) halogen lamp. As Clearvision Darkstar 95F.

### Darkstar 95 A:

A recessed single lamp 97mm diameter x 84mm deep tilt/rotational spotlight to suit a 80mm ceiling cut out. Die-cast, powder-coated white (RAL 9010) aluminium bezel. Spun, black painted aluminium. 20 degree tilting, anti-glare, barrel. Magnetically held, fully 360 degree rotating bezel. 2-way terminal block with clip-close enclosure, located on a steel mounting arm. 2off sprung steel fixing arms suitable for ceilings of up to 25mm thickness. Supplied with dimmable electronic transformer to operate a single 20-50w MR16 (50mm dia.) halogen lamp. As Clearvision Darkstar 95A.

### Darkstar 75 F:

A recessed single lamp 75mm diameter x 100mm deep tilt/rotational spotlight to suit a 60mm ceiling cut out. Die-cast, powder-coated white (RAL 9010) aluminium bezel. Spun, black painted aluminium, anti-glare, barrel. Magnetically held, fully 360 degree rotating bezel. 2-way terminal block with clip-close enclosure, located on a steel mounting arm. 2off sprung steel fixing arms suitable for ceilings of up to 25mm thickness. Supplied with dimmable electronic transformer to operate a single 20-35w MR11 (35mm dia.) halogen lamp. As Clearvision Darkstar 75F.

### Darkstar 75 A:

A recessed single lamp 75mm diameter x 94mm deep tilt/rotational spotlight to suit a 60mm ceiling cut out. Die-cast, powder-coated white (RAL 9010) aluminium bezel. Spun, black painted aluminium. 20 degree tilting, anti-glare, barrel. Magnetically held, fully 360 degree rotating bezel. 2-way terminal block with clip-close enclosure, located on a steel mounting arm. 2off sprung steel fixing arms suitable for ceilings of up to 25mm thickness. Supplied with dimmable electronic transformer to operate a single 20-35w MR11 (35mm dia.) halogen lamp. As Clearvision Darkstar 75A.