

Clearvision Lighting - Specification

LED Line (5400k):

A surface mounted linear LED kit comprising; 1off 2.8m reel of 120 no. power 24volt 72watt LEDs mounted to a flexible, self-adhesive substrate. Reel is divisible at 140mm intervals. 5400k, 964 lumens/m. LED life rated at 60,000 hours. 2off 1424 x 35.5 x 37.7mm (LxWxH) lengths of anodised aluminium track complete with acrylic clip-on diffuser covers. 4off clip-in, sliding metal fixing brackets with securing slot. 2off acrylic push-on endcaps. 1off 241mm x 43mm x 30mm 120-277volt (primary), 24volt (secondary) 75watt SELV smart power supply unit. Power supply life rated at 50,000 hours. 1off power supply to LED connector (500mm leads). 1off flexible LED to LED coupling connector (34.5mm). As Clearvision LED Line.

LED Line (2700k):

A surface mounted linear LED kit comprising; 1off 2.8m reel of 120 no. power 24volt 72watt LEDs mounted to a flexible, self-adhesive substrate. Reel is divisible at 140mm intervals. 2700k, 535 lumens/m. LED life rated at 60,000 hours. 2off 1424 x 35.5 x 37.7mm (LxWxH) lengths of anodised aluminium track complete with acrylic clip-on diffuser covers. 4off clip-in, sliding metal fixing brackets with securing slot. 2off acrylic push-on endcaps. 1off 241mm x 43mm x 30mm 120-277volt (primary), 24volt (secondary) 75watt SELV smart power supply unit. Power supply life rated at 50,000 hours. 1off power supply to LED connector (500mm leads). 1off flexible LED to LED coupling connector (34.5mm). As Clearvision LED Line.