

## Clearvision Lighting - Specification

### Circle:

A recessed dual lamp 400mm diameter x 150mm deep feature downlight to suit a 385mm ceiling cut out. Spun, powder-coated matt black aluminium body. White painted bezel. Polished aluminium reflector. Grey polymer anti-glare outer ring louvre. Opal acrylic inner circular diffuser. 4off sprung steel fixing arms suitable for ceilings of up to 25mm thickness. Supplied with high frequency electronic control gear to operate a single 40/55w\* T5 circular (outer) lamp and a 26/32w\* TC-TEL compact fluorescent (centre) lamp. As Clearvision Circle.

\* Delete as appropriate.

### Circle LED:

A recessed dual lamp 400mm diameter x 150mm deep feature downlight to suit a 385mm ceiling cut out. Spun, powder-coated matt black aluminium body. White painted bezel. Polished aluminium reflector. Grey polymer anti-glare outer ring louvre. Opal acrylic inner circular diffuser housing a 1.2w white LED. 4off sprung steel fixing arms suitable for ceilings of up to 25mm thickness. Supplied with high frequency electronic control gear to operate a single 40/55w\* T5 circular (outer) lamp and driver to operate the LED. As Clearvision Circle.

\* Delete as appropriate.

### Circle LED RGB:

A recessed dual lamp 400mm diameter x 150mm deep feature downlight to suit a 385mm ceiling cut out. Spun, powder-coated matt black aluminium body. White painted bezel. Polished aluminium reflector. Grey polymer anti-glare outer ring louvre. Opal acrylic inner circular diffuser housing a 2.5w RGB LED array. 4off sprung steel fixing arms suitable for ceilings of up to 25mm thickness. Supplied with high frequency electronic control gear to operate a single 40/55w\* T5 circular (outer) lamp and driver to operate the LED array. As Clearvision Circle.

\* Delete as appropriate.