

Clearvision Lighting - Specification

Screen Recessed:

A recessed single lamp 376mm x 92mm x 114mm high emergency exit sign to suit a 70mm x 360mm ceiling cutout. 3 hour minimum duration. Replaceable NiMh battery pack. Galvanised steel gear enclosure with 2x flip out and screw down fixing paddles. Silver polyester powder coated/stainless steel* finish bezel. Clear edge-lit polycarbonate legend blade. Clip-in removable bezel and legend blade (325mm x 175mm x 8mm) assembly for easy lamp access. Green LED charge indicator. 2x pictograms to suit installation location. Supplied with high frequency electronic control gear to operate 1x8w T5 linear fluorescent lamp. As Clearvision Screen Recessed.

* Delete as appropriate.

Screen Surface:

A surface mounted single lamp 328mm x 40mm x 105mm high emergency exit sign. 3 hour minimum duration. Replaceable NiMh battery pack. Galvanised steel gear spine. Silver polyester powder coated/stainless steel* finish casing. Clear edge-lit 325mm x 173mm x 8mm thick polycarbonate legend blade. 2x pictograms to suit installation location. Supplied with high frequency electronic control gear to operate 1x8w T5 linear fluorescent lamp. As Clearvision Screen Surface.

* Delete as appropriate.

Additions

Self test facility
1.2w LED light source.