

Clearvision Lighting - Specification

Corona 2:

A recessed 1/2/3/4* lamp 596mm x 596mm x 105mm deep direct/indirect luminaire to suit suspended exposed T grid and plasterboard ceilings. White (RAL 9003) powder-coated, mild steel body, removable gullwing reflectors and perforated flush basket. Central basket houses a flat 'Optika' Virtual Daylight® polarising polycarbonate lens. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 1x55w/2x40w TC-L compact fluorescent lamps*/3/4x14w T5 linear fluorescent lamps*

As Clearvision Corona 2.

* Delete as appropriate.

Corona 2 Metal Ceiling:

A recessed 1/2/3/4* lamp 596mm x 596mm x 105mm deep direct/indirect luminaire to suit suspended concealed grid, metal tile and plasterboard ceilings. White (RAL 9003) powder-coated, mild steel body, removable gullwing reflectors and perforated flush basket. Central basket houses a flat 'Optika' Virtual Daylight® polarising polycarbonate lens. 4x Lumafix Fixing arms for offer-up installation. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 1x55w/2x40w TC-L compact fluorescent lamps*/3/4x14w T5 linear fluorescent lamps* As Clearvision Corona 2.

* Delete as appropriate Metal Ceiling.

Additions

3 hour maintained emergency facility.

20 litres/second return air handling facility

4x Fixing arms for offer-up installation