

Clearvision Lighting - Specification

SR 600x600:

A recessed 2/3/4* lamp 598mm x 598mm x 140mm deep offer up luminaire. White (RAL 9003) powder-coated, mild steel body. Polycarbonate Virtual Daylight® polarising lens with white PVC edging detail to locate via a lift and tilt method within the luminaire aperture. High efficiency 'DRS' internal reflector system. 4x Lumafix fixing arms. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 3/4x14w* T5 linear fluorescent lamps/2x40w TC-L compact fluorescent lamps*. As Clearvision SR6.

* Delete as appropriate.

SR 300x1200:

A recessed twin lamp 1198mm x 298mm x 111mm deep offer up luminaire. White (RAL 9003) powder-coated, mild steel body. Polycarbonate Virtual Daylight® polarising lens with white PVC edging detail to locate via a lift and tilt method within the luminaire aperture. High efficiency 'DRS' internal reflector system. 4x Lumafix fixing arms. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 2x28/54w* T5 linear fluorescent lamps. As Clearvision SR3.

* Delete as appropriate.

SR 600x1200:

A recessed twin lamp 1198mm x 598mm x 111mm deep offer up luminaire. White (RAL 9003) powder-coated, mild steel body. Polycarbonate Virtual Daylight® polarising lens with white PVC edging detail to locate via a lift and tilt method within the luminaire aperture. High efficiency 'DRS' internal reflector system. 4x Lumafix fixing arms. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 4x28w T5 linear fluorescent lamps. As Clearvision SR6.

* Delete as appropriate.

Additions

3 hour maintained emergency facility.

45 degree chamfered bezel.

Slotted bezel to achieve 40 litres/second return air handling.