

Clearvision Lighting - Specification

Sky2 FX:

A surface/suspended Eight lamp 1245mm x 1245mm x 200mm deep large format square luminaire. White (RAL 9003) powder-coated, mild steel body. Hinged opening frame housing an opal stretched membrane diffuser. Frame secured by 4 off shoot bolts. 4x corner wire/rod suspension points in back of housing. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 8x28/54w* T5 linear fluorescent lamps. As Clearvision Sky2 FX.

* Delete as appropriate.

Sky2 FX RGBW:

A recessed Ten lamp 1245mm x 1245mm x200mm deep large format square luminaire. White (RAL 9003) powder-coated, mild steel body and bezel. Hinged frame housing an opal stretched membrane diffuser. Frame secured by 4 off shoot bolts. 4x corner wire/rod suspension points in back of housing. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 2x28/54w* Red, 2x28/54w* Green, 2x28/54w* Blue and 4x28/54w* White 6500k T5 linear fluorescent lamps. As Clearvision Sky2 FX RGBW.

* Delete as appropriate.

Sky2 FX Circada:

A recessed Eight lamp 1197mm x 1197mm x200mm deep large format square luminaire. White (RAL 9003) powder-coated, mild steel body and bezel. Hinged frame housing an opal stretched membrane diffuser. Frame secured by 4 off shoot bolts. 4x corner wire/rod suspension points in back of housing. Integral control gear. Fused terminal block. Supplied with high frequency electronic control gear to operate 4x28/54w* 2700k and 4x28/54w* 6500k White T5 linear fluorescent lamps. As Clearvision Sky2 FX Circada.

* Delete as appropriate.

Additions

3 Hour maintained integral emergency facility

4-point stainless steel, clutch type, adjustable drop, wire suspensions.